Specifications



Eaton C10M25

Eaton Bussmann series low voltage 10 x 38 mm cylindrical/ferrule fuse, rated at 400 Volts AC, 25 Amps, 120 kA Breaking capacity, class aM, without indicator, compatible with a CHM Modular fuse holder

General specifications	
PRODUCT NAME	Eaton Bussmann series low voltage cylindrical fuse
CATALOG NUMBER	C10M25
EAN	5027590493703
UPC	051712754620
PRODUCT LENGTH/DEPTH	38 mm
PRODUCT HEIGHT	10 mm
PRODUCT WIDTH	10 mm
PRODUCT WEIGHT	8.2 g
COMPLIANCES	CE Marked GoST-R RoHS Compliant
CERTIFICATIONS	IEC 60269
MODEL CODE	CYLINDRICAL FUSE 10 x 38 25A AM 400V AC

Powering Business Worldwide

Electrical data

AMPERAGE RATING	25 A
VOLTAGE RATING	400 V
VOLTAGE TYPE	AC
BREAKING CAPACITY	120 kA
UTILIZATION CATEGORY	aM (switchgear protection)
FREQUENCY RATING - MAX	62 Hz

Compatible fuse holder

SUITABLE FOR	CHM Modular fuse holder

Resources

CATALOGUES	eaton-bussmann-series-low-voltage-fuses-catalog-ca134002en-en-us.pdf eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf
DECLARATIONS OF CONFORMITY	eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-uk250946en.pdf eaton-low-voltage-cylindrical-fuse-declaration-of-conformity-eu250463en.pdf
MULTIMEDIA	Video Cylindrical fuse link portfolio
TECHNICAL DATA SHEETS	720115 Cylindrical fuses

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.